

ADPV60F (16V/1.0A)

SPECIAL FEATURES	
※ Universal AC input	※ High efficiency
※ Low output ripple	※ Built-in EMI filter
※ Short circuit protection	※ Over load protection

INPUT	
Input range	85 ~ 264 VAC
Input frequency	47 ~ 63 Hz
Inrush current	<15A at 115VAC; <30A at 230VAC; cold start at 25°C
Input current	1.5A Max
Leakage current	<0.5 mA at 50/60 Hz 264VAC input

OUTPUT	
Rated output power	16 Watts
Output voltage	16 V ±4% (15.60V ≤ V _{output} ≤ 16.40V)
Output current	1.0A
Output load efficiency	≥80% at 90VAC full load; ≥80% at 264VAC full load
Max power	16 Watts for convection
Adjustment range	fixed
Hold-up time	30 ms at full load and 230 VAC nominal line
OL protection	96% to 104% above peak rating
Ripple & noise	≤100mV at rated load
Short current	≤40mA at 250 VAC rated load

ISOLATION	
Input to output	AC3.0 KV/1 min.
SAFETY APPROVAL	
CE CCC UL	

ENVIRONMENTAL	
Operating temp.	0 °C to 50 °C ambient derate each output at 4.0% per degree from 50 °C to 60 °C
Storage temp.	-40 °C to 85 °C
Operating humidity	5% to 95% (non-condensing)
MTBF	100,000 hours at full load and 25 °C ambient conditions (demonstrated)
Size	65 × 52 × 29

Special specification can be provided on customer's request

OUTSIDE FRAME DRAWING

HGPOWER®

