BC1206

BATTERY CHARGER

















Color: CE FC D





产品参数

PRODUCT PARAMETER

SPECIFICATIONS	
Туре	Smart & Automatic
AC Input	100-240V 50/60Hz
Output Voltage	12V
Output Current	12V 6A
Output volt No Load	14.6V
Minimum Start Volt	>5.0V
Input Power With Load	Max.90W
Input Power No Load	1.3W
Cooling	Fan
Size (L*W*H)	158*90*65mm
Net Weight	415 g
Approval	CE/FCC/RoHS

产品功能 PRODUCT FUNCTION

【QUICK BATTERY CHARGER】 12V 6-Amp quick battery charger. MCU controller monitor the whole charging progress, Suitable for charging and repairing all 12V lead-acid batteries, including AGM, GEL, SLA, and Flooded types, in cars, trucks, SUVs, motorcycles, lawnmowers, boats, and more.

[High-Efficiency Pulse Repair] Advanced pulse repair functionality. The battery charger utilizes a slow pulse repair technique to automatically detect battery sulfation and acid stratification, achieving stronger engine starts and longer battery life. It restores the performance loss of batteries, assists in repairing old/idle batteries, and prolongs battery life.

[Temperature Detection & Flame-Retardant Design] Monitors battery temperature in real-time and is built with flame-retardant materials for added safety and durability.

[Multi-Protection Safety System] Offers comprehensive safety features, including over-temperature, over-current, high/low voltage, and short-circuit protection, ensuring safe and reliable charging

[Smart LCD Display] Features a clear LCD screen that shows real-time charging status, voltage, and temperature, providing you with all the information you need at a glance