

REF: 03B803X18B0 S'CE (EMC), :: UL, :: CE (LVD)

BM803

1000A AC/DC AUTO-RANGING

- 3 3/4 digits LCD display, max. reading 3999
- Versatility of use with AC/DC voltage & current, resistance, capacitance, frequency (up to 20MHz) and pulse duty measurement
- Relative measurement
- Data hold, auto-power off
- Safety as per IEC1010-1 CAT.II 1000V

Technical specifications

DCV: 400m/4/40/400/1000V, ±0.8%

ACV: 400m/4/40/400/700V, ±1.2%

DCA: 40m/100mA, ±1.5% (optional) 400/1000A, ±2.0%

400/1000A, ±2.0% ACA: 40m/100mA, ±1.0% (optional)

400/1000A, $\pm 1.9\%$ OHM: 400/4k/40k/400k/4M/40M $_{\Omega}$, $\pm 1.0\%$

CAP: $40n/400n/4 \mu /40 \mu /100 \mu F$, $\pm 3.0\%$ FREQ: 40/400/4k/40k/400k/4M/20MHz, $\pm 0.5\%$ Pulse Duty: $0.1\% \sim 99.9\%$

Audible continuity & diode test

Clamp size: 54mm (max.) Battery: 1.5Vx2, AA size

Dimensions & weight: 248x88x45mm, 360g Accessories: carrying bag

Accessories: carrying bag