

4	pin header	Copper alloy	Sn Plated
3	Spring	Stainless steel	/
2	Screw	Steel	M2.5/Zn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/10	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	250/17.5	/
工频耐压/Withstanding voltage(V/1min)	AC2000		
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M2.5, 0.3/2.6		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm ²)	26~14 / 0.5~1.5		
间距/Pitch(mm)/线数范围/Poles	5.0/N=02~24P		
剥线长度/Stripping length(mm)	6~7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

 DEGSON		MATERIAL:		SURFACE/COLOR:	
		MAT NO./REV:		MAT STATUS: 批量	
APPD: 兰春华	2023.04.03	NAME DG126-5.0-XXP-1Y-02A(H)			
CHKD: 陈招	2023.04.03				
DRFT: 龚徐涛	2023.03.31	DRAWING NO. 200029637	TYPE CUSTOMER DRAWING	DRAWING STATUS 已发布	SCALE 4:1
 A4	 1(inch)	SHEET 1/1			

00			龚徐涛	2023.03.3
REV	ECN	DESCRIPTION	DRFT	DATE