

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 未经许可，不得复制或传播本文件内容，否则将承担法律责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1755 Rev.1.3

2



3

4


5

6

Positive pole “+”
Negative pole “-”



Other wiring forms: Form 1:




ESS-120A-25-X-XX-00


Color: BK : Black
OR : Orange
RD : Red

Contact Termination: B : Busbar
C : Crimp
S : Screw
B/S : Copper Screw



Form 2:



Only in the form of Busbar 3D display:



Form 3:



Recommended
Panel Cut-Out

Dimensional tolerance(mm)						0.1/10 ±2'
0	>30	>60	>100	>150		
~30	~60	~100	~150			
±0.25	±0.35	±0.55	±0.80	±1.10		

Technical requirements:	
Color	Black, Orange, Red
Locking method	Buckle
Terminal	Busbar, Screw, Crimp, Copper Screw
Housing material	PA+GF
Connector material	Copper alloy
Insertion force	60N Max
Withdrawal force	>10N
Mechanical working life(mating cycles)	100
Screw torque	M4/0.4~0.7N.m
Wiring specifications	4AWG or 25mm²
Suggested stripping length	13~14mm (Crimp type)
Wire diameter	9~10.3mm (Crimp type)
Rated voltage	1500V DC
Rated current	120A
Insulate resistance	≥5000MΩ (drying)
Withstanding voltage	6800V/min
Contact resistance	≤0.5mΩ
Overvoltage category	III
Pollution degree	3
Ingress protection	IP67(Mated)
Operating temperature(° C)	-40~+125(including temperature rise)
Salt spray	48H
Storage temperature(° C)	-40~+85
Flame retardant ability	UL94-V0
Conform to RoHS	Yes
ULA128 certification	E526028
TUV certification	50581738

			MATERIAL:		SURFACE:		
			MAT. NO./REV: /		MAT. STATUS:		
APPD:			NAME ESS-120A-25-X-XX-00L(H)				
CHKD:							
DRFT:	Zhang XY	2024.09.19	DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
 A4						CUSTOMER DRAWING	1:1
							1/1

1

2

3

4

5

6