

1		2		3		4		5		6		7		8																																																																	
RoHS Compliance												REV		SYM		Revision Record		Appr.		Date																																																											
												V0		KLS17120		New Version Release		Song		2026-09-29																																																											
1500±20 3 1 2																																																																															
<table><tr><td>3</td><td>Connector</td><td colspan="2">6.35 Mono Male Head</td><td>1</td></tr><tr><td>2</td><td>Connector</td><td colspan="2">RCA male head</td><td>1</td></tr><tr><td>1</td><td>Wire</td><td colspan="2">2464-20AWG 28/0.15BC, OD4.3mm</td><td>1</td></tr><tr><td>NO.</td><td>NAME</td><td colspan="2">TYPE</td><td>Quantity</td></tr></table>																				3	Connector	6.35 Mono Male Head		1	2	Connector	RCA male head		1	1	Wire	2464-20AWG 28/0.15BC, OD4.3mm		1	NO.	NAME	TYPE		Quantity																																								
3	Connector	6.35 Mono Male Head		1																																																																											
2	Connector	RCA male head		1																																																																											
1	Wire	2464-20AWG 28/0.15BC, OD4.3mm		1																																																																											
NO.	NAME	TYPE		Quantity																																																																											
Technical Requirements: 1. Electrical performance: The product undergoes 100% electrical conductivity testing and must not have short circuits, misalignment, poor contact, or other phenomena. 2. Appearance: The wire color is uniform, and the surface of the sheath is free of defects such as damage, scratches, dirt, deformation, etc. 3. All materials comply with ROHS and other requirements.																																																																															
<table><tr><td colspan="2">ANGLE TOLERANCE</td><td colspan="2">PROJECTION</td><td colspan="2">Description:</td><td colspan="4">Wire harness</td></tr><tr><td colspan="2">±3°</td><td colspan="2"></td><td colspan="2"></td><td colspan="4"></td></tr><tr><td colspan="2">GENERAL TOLERANCE</td><td colspan="2">UNITS</td><td colspan="2">mm</td><td colspan="2">KLS P/N:</td><td colspan="4">L-KLS17-MRP-01-6.3-1.50M</td></tr><tr><td colspan="2">x.x ±0.30</td><td colspan="2">SHEET SIZE</td><td colspan="2">A4</td><td colspan="2"></td><td colspan="4" rowspan="3"> NingBo KLS ELECTRONIC CO.,L TD.</td></tr><tr><td colspan="2">x.xx ±0.20</td><td colspan="2">Draw:</td><td colspan="2">Song</td><td colspan="2">2026-09-29</td></tr><tr><td colspan="2">x.xxx ±0.10</td><td colspan="2">Check:</td><td colspan="2">Daniel</td><td colspan="2">2026-09-29</td></tr></table>																				ANGLE TOLERANCE		PROJECTION		Description:		Wire harness				±3°										GENERAL TOLERANCE		UNITS		mm		KLS P/N:		L-KLS17-MRP-01-6.3-1.50M				x.x ±0.30		SHEET SIZE		A4				NingBo KLS ELECTRONIC CO.,L TD.				x.xx ±0.20		Draw:		Song		2026-09-29		x.xxx ±0.10		Check:		Daniel		2026-09-29	
ANGLE TOLERANCE		PROJECTION		Description:		Wire harness																																																																									
±3°																																																																															
GENERAL TOLERANCE		UNITS		mm		KLS P/N:		L-KLS17-MRP-01-6.3-1.50M																																																																							
x.x ±0.30		SHEET SIZE		A4				NingBo KLS ELECTRONIC CO.,L TD.																																																																							
x.xx ±0.20		Draw:		Song		2026-09-29																																																																									
x.xxx ±0.10		Check:		Daniel		2026-09-29																																																																									
1		2		3		4		5		6		7		8																																																																	