


Voltage	DC12V	DC24V
Current	1.8A	1.5A
Power	21.6W	36W
Power on hours	≤5S the recommended power-on interval is more than 3 minutes	
Suction of lock tongue	Initial suction:1.5N Holding suction: 10N	
Stroke of lock tongue	10mm	
Operative mode	Power-on pull-in power-off eject	
Specific performance	/	
Insulation withstand voltage	600VAC/15sec	
Insulation resistance	500VDC/100MΩ	
Insulation grade	F (155℃)	
Use environment	-20℃~+40℃, humidity:5-90%	

RECOGNITION	DESIGNER	CONFIRMOR	VERSION	CHANGE CONTENT	CHANGE PERSON	DATE	The materials and surface treatments used in this product are in compliance with ROHS specifications	General tolerance	LESS THAN 60	±0.1	PROPORTION	 THIRD PERSPECTIVE			
									6~30	±0.2	1:1				
									30~60	±0.3	UNIT	MODEL	LT-03T		
									GREATER THAN 60	±0.4	mm				
									THICKNESS	Ra3.2	R ANGLE	Appearance size chart			
							CONCENTRICITY		±0.1	0.1					
							FLATNESS		±0.1	CHAMFER					
							VERTICALITY		±0.1	0.1*45°					