

Digital Multimeter - True RMS

MS8239T



- Frequency: 1000Hz
- Overload Protection
- True RMS
- Diode
- Continuity Check
- LED
- Non-Contact Voltage (NCV) Detection / Live Wire (Live) Recognition
- Max Display: 4000
- CAT III 600V
- MAX / MIN / Relative
- Auto Power Off / Data Hold / Backlight / Unit Display
- Battery: 1.5V AAA*2

MS8239T

Spec	Range	Accuracy	Spec	Range	Accuracy
Resistance	400Ω	±(1.2%+2)	AC Current	400uA	±(1.8%+3)
	4KΩ, 40KΩ, 400KΩ, 4MΩ	±(1.0%+2)		4000uA, 40mA	±(1.5%+5)
	40MΩ	±(1.2%+8)		400mA	±(2.5%+5)
DC Voltage	40mV	±(0.5%+5)	4A, 10A	±(3.0%+10)	
	400mV	±(0.5%+3)	Frequency	10MHz	±(0.1%+2)
	4V, 40V, 400V	±(0.8%+3)	°C	-20 °C ~ 750 °C	±(2.0%+3)
	600V	±(1.0%+5)	°F	-4 °F ~ 1832 °F	±(3.0%+3)
AC Voltage	40mV	±(1.0%+20)	Capacitance	40.00nF	±(4.0%+25)
	400mV	±(1.0%+10)	400.0nF ~ 400.0uF	±(4.0%+15)	
	4V, 40V, 400V	±(0.8%+3)	4.000mF ~ 40.00mF	±(5.0%+25)	
	600V	±(1.2%+5)	Frequency	4.000Hz ~ 10MHz	±(0.1%+2)
DC Current	400uA, 4000uA, 40mA	±(1.0%+5)			
	400mA	±(2.0%+5)			
	4A, 10A	±(2.5%+5)			

Packaging Information	
Accessories	Test leads, Manual, Temperature probe, 1.5V*2 AAA Battery
Dimension	147mm*74mm*46mm
Weight	229g
Quantity	40
Color Box	112mm*54mm*155mm
Carton Box	515mm*290m*400mm
SKU No.	MS8239TCBGLO
EAN Code	8435394788326

MGL Global Solutions (China) Company Limited

R72, Puxing East Road, Qingxi, Dongguan, Guangdong, China
 400-099-1987
 cs@mastech.cn



WeChat Official Account

www.mastech-group.com