

Digital Multimeter - True RMS

MS8239D+



- Frequency 1000Hz
- Overload Protection
- True RMS
- Diode/Continuity/ LED
- Non-Contact Voltage (NCV) Detection / Live Wire(Live) Recognition
- Max Display: 4000
- CAT III 600V
- MAX / MIN
- Relative
- Auto Power Off / Data Hold / Backlight / Unit Display
- Battery: 1.5V AAA*2

MS8239D+

Spec	Range	Accuracy	Spec	Range	Accuracy
Resistance	400Ω	±(1.2%+2)	ACA	400uA	±(1.8%+3)
	4KΩ, 40KΩ, 400KΩ, 4MΩ	±(1.0%+2)		4000uA, 40mA	±(1.5%+5)
	40MΩ	±(1.2%+8)		400mA	±(2.5%+5)
DCV	40mV	±(0.5%+5)	Capacitance	4A, 10A	±(3.0%+10)
	400mV	±(0.5%+3)		40.00nF	±(4.0%+25)
	4V, 40V, 400V	±(0.8%+3)		400.0nF~400.0uF	±(4.0%+15)
	600V	±(1.0%+5)	4.000mF~40.00mF	±(5.0%+25)	
	40mV	±(1.0%+20)	Frequency	4.000~10MHz	±(0.1%+2)
400mV	±(1.0%+10)				
ACV	4V, 40V, 400V	±(0.8%+3)			
	600V	±(1.2%+5)			
	400uA, 4000uA, 40mA	±(1.0%+5)			
DCA	400mA	±(2.0%+5)			
	4A, 10A	±(2.5%+5)			

Packaging Information	
Accessories	Test leads, Manual, 1.5V*2 AAA Battery
Dimension	147*74*46mm
Weight	229g
Quantity	40
Color Box	112*54*155mm
Carton Box	570*335*250mm
SKU No.	MS8239D+CBGLO
EAN Code	8435394788319