

Digital Multimeter

MS830N



- Frequency: 400Hz
- Diode Test
- Continuity Check
- Transistor Test
- LED
- Non-Contact Voltage (NCV) Detection / Live Wire (Live) Recognition
- Max Display: 2000
- Overload Protection
- Unit Display
- CAT III 600V
- Auto Power Off
- Data Hold
- Backlight
- Battery: 1.5V AAA*2

MS830N

Spec	Range	Accuracy
Resistance	200Ω, 2KΩ, 20KΩ, 200KΩ	±(1.0%+5)
	20MΩ	±(1.2%+8)
DC Voltage	200mV	±(0.5%+3)
	2V, 20V, 200V, 600V	±(0.8%+5)
AC Voltage	200V, 600V	±(1.0%+10)
	20mA	±(1.0%+5)
DC Current	200mA	±(2.0%+5)
	10A	±(3.0%+5)
Battery Test	1.5V, 3V, 9V	±(1.8%+2)

Packaging Information	
Accessories	Test leads, Manual, 1.5V*2 AAA Battery
Dimension	133mm*71mm*47mm
Weight	190g
Quantity	40
Color Box	112mm*54mm*155mm
Carton Box	495mm*310mm*465mm
SKU No.	MS830NCBGLO
EAN Code	8435394788296

MGL Global Solutions (China) Company Limited

R72, Puxing East Road, Qingxi, Dongguan, Guangdong, China
 400-099-1987
 cs@mastech.cn



WeChat Official Account

www.mastech-group.com