

Model	P35-C2GB-2MP000C4GEU	P35-C2GB-5MP000C4GEU	P35-C2GB-8MP000C4GEU
Camera Effective pixels	2MP 1080p(1920*1080)	5MP(2560*1920)	8MP 4K (3840*2160)
CMOS Sensor	1/2.7"	1/2.8"	1/2.8"
Lens	3.6mm Lens(4X Digital)		
View angle	90°		
Min.illumination	0.05 Lux / 0 Lux(IR on)		
Day&Night mode	Auto IR-CUT		
Night vision distance	15pcs Array Infrared LEDs,15pcs White light LEDs Full color night vision SUPPORT		
Video compression Standard	H.264/H.265		
Video streaming	Triple streaming		
Video resolution	First stream:1920*1080 Main Stream		
	Second stream:VGA		
	Triple stream :QVGA		
Image settings	Brightness,saturation,contrast,Sharpness,Exposure,flip,mirror		
Image enhancement	Backlight compensation,Automatic white balance,Digital WDR, 3D digital noise reduction		
Audio function	Built in Audio Microphone, Support Two Way Audio Talk Back		
Motion detecting	Can set 4 independent detection region (1-100 sensitivity can be set)		
Alarm linkage	Alarm send pictures to the specified mailbox,		
	alarm upload pictures and videos to the FTP server,		
	alarm write pictures and videos to Micro TF card, alarm message push		
Privacy mask	Maximum support 4 users to simultaneously browse		
OSD	Support camera name, date and time information superimposed		
User management	Supports user and rights management		
Simultaneous viewers	maximum support 12 users to simultaneously browse (each stream supports 4 users)		
Network protocol	TCP/IP,HTTP,TCP,ICMP,UDP,ARP,IGMP,SMTP,		
	FTP,DHCP,DNS,DDNS,NTP,UPNP,RTSP (Customization required) etc.		
Connection protocol	ONVIF-Compatible 2.1Version (backward compatible)(4G Version not supported)		

Network Support	2.4 GHz to 2.4835 GHz / IEEE802.11b/g/n Draft(4G Version not supported)	GSM 900/1800 MHz ; 4G FDD-LTE Band 1/3/7/8/20 ; 4G TDD-LTE Band 38/40/41 ; 3G WCDMA Band 1/8(WIFI Version not supported)
Wireless Security	64/128-bit WEP. WPA/WPA2. WPA-PSK/WPA2-PSK. WPS	
Transmission rate	11b: 11Mbps, 11g :54Mbps, 11n :135Mbps	
Rotation angle	Horizon: 355°. Vertical: 0° to 90°	
Horizontal speed	1° to 30°/S	
Vertical speed	1° to 15°/S	
Cruise Zoom	Not Support	
Power interface	1* DC ϕ 2.1*5.5mm power interface	
Ethernet	1 * RJ45 & Antenna 10M/100M Adaptive Ethernet Interface (4G Version not supported)	
TF card Slot	1 * TF card slot. up to 256GB (NOT included TF Card)	
Reset button	Support	
Power supply	DC 12V 2A	
Power	Day: 3W; Night: 10W	
Operating temperature	-20 to +60 degree	
Operating humidity	10% to 95%	
Material&Waterproof Level	Metal Housing ,Outdoor Use,Waterproof IP66	
Installation	Wall mounting	
Size(W×D×H)(mm)	185(mm)× Φ 125(mm)×240(mm)	
Weight(kg)	0.7kg	
Package Size(mm)	245*225*181	
Package Weight(kg)	1.2kg	