

SPECIFICATION FOR APPROVAL

Polypropylene Film Capacitor (High Voltage) – PPS Series								
Customer :			Issue No.					
Capacitance : 0.0022 uF		Tolerance: ±10 %		Issue Day. 23/06/2020				
Lot No.		Part No. PPS222K3CB		W V 1600 VDC				
Diagram of Dimensions : (Unit : mm)								
			W: <u>25.0 max.</u> H: <u>15.0 max.</u> T: <u>8.0 max.</u> P: <u>21.0 ±1.25</u> d: <u>0.80 ±0.05</u>					
SPECIFICATION				Initial Test				
				No.	uF	Tanδ	I.R.	T.V.
1	Operating Temperature Range : -40°C to +105°C			1.				
2	Dissipation Factor : 0.1% Max. at 1KHz , 20°C			2.				
3	Insulation Resistance : Between Terminal ≥ 30,000 MΩ			3.				
4	Dielectric Strength Test : 2800 VDC for 1 ~ 5 Sec.			4.				
5	Solderability : 260°C ± 5°C in 3 sec.			5.				
6	Flame-Retardant Epoxy Resin Coating (UL 94V-O)			6.				
				7.				
				8.				
				9.				
				10.				
APPROVED BY CUSTOMER				REMARK :				
Your Confirmation : ☐ Approval ☐ Conditional Approval ☐ Rejection (Please send a copy for our ref.)				For further details please visit the following link of our website: PPS_20191206.pdf				
Inspected by		Checked by		吳美華 Approved by 許介洲				