


Specifications

Nominal Voltage		12 V
Capacity (25°C)	10HR(10.5V)	150Ah
	5HR(10.2V)	116.5Ah
	1HR(9.6V)	87.3Ah
Dimension	Length	485±2mm (19.09inch)
	Width	172±2mm (6.77inch)
	Height	240±2mm (9.45inch)
	Total Height	240±2mm (9.45inch)
Approx. Weight		42.0kg (92.5lbs) ±4%
Terminal type		T14
Internal resistance (Fully charged, 25°C)		Approx. 4.2mΩ
Capacity affected by temperature (10HR)	40°C	103%
	25°C	100%
	0°C	88%
	-15°C	70%
Self-discharge (25°C)	3 month	Remaining Capacity: 94%
	6 month	Remaining Capacity: 88%
	12 month	Remaining Capacity: 75%
Nominal operating temperature		25°C±3°C(77°F±5°F)
Operating temperature range	Discharge	-15°C~55°C(5°F~131°F)
	Charge	-10°C~55°C(14°F~131°F)
	Storage	-20°C~55°C(-4°F~131°F)
Float charging voltage(25°C)		13.50 to 13.80V Temperature compensation: -18mV/°C
Cyclic charging voltage(25°C)		14.10 to 14.40V Temperature compensation: -30mV/°C
Maximum charging current		30A
Terminal material		Copper
Maximum discharge current		1500A(5 sec.)
Designed floating life(20°C)		15 years


- Gelled electrolyte technology;
- PVC separator;
- Recognized by CE;
- ABS container.



Dimensions



Terminal



Constant Current Discharge Characteristics (A, 25°C)


F.V/TIME	15min	30min	60min	2h	3h	4h	5h	6h	8h	10h	20h
9.60V	250	152	93.9	54.8	38.3	31.4	26.8	23.4	18.4	15.3	8.02
9.90V	244	148	92.5	54.5	38.0	31.2	26.6	23.3	18.3	15.2	8.00
10.2V	235	144	90.2	54.0	37.8	31.0	26.4	23.1	18.1	15.2	7.98
10.5V	227	140	88.4	53.2	37.5	30.8	26.3	23.0	18.0	15.1	7.93
10.8V	215	135	85.7	51.8	36.4	29.8	25.5	22.3	17.5	15.0	7.88

Constant Power Discharge Characteristics (Watt, 25°C)


F.V/TIME	15min	30min	60min	2h	3h	4h	5h	6h	8h	10h	20h
9.60V	2745	1700	1071	635	450	369	316	277	218	182	96.2
9.90V	2679	1666	1055	631	447	367	315	275	217	182	96.0
10.2V	2580	1615	1028	625	444	364	312	273	215	181	95.7
10.5V	2492	1576	1008	616	441	362	310	271	214	180	95.2
10.8V	2360	1518	977	600	428	351	301	263	207	179	94.5

Note: The above characteristics data can be obtained within three charge/discharge cycles.


Discharge Characteristics(25°C)




Charging Characteristics(25°C)




Effect of Temperature on Capacity




Self-discharge Characteristics




The Relationship for Open Circuit Voltage and Residual Capacity (25°C)



The Relationship for Charging Voltage and Temperature



Floating Life on Temperature



Cycle Life on D.O.D(25°C)

