

Specifications	UT136D (original UT36D)	
Basic functions	Range	Basic accuracy
DC voltage	400mV/4V/40V/400V/500V	± (0.8% +1)
AC voltage	400mV/4V/40V/400V/500V	± (1.2% +3)
DC current	400uA/4mA/40mA/400mA/4A/10A	± (1.0% +2)
AC Current	400uA/4mA/40mA/400mA/4A/10A	± (1.2% +5)
Resistance	400Ω/4000Ω/40kΩ/400kΩ/4MΩ/40MΩ	± (1.0% +2)
Capacitance	4nF/40nF/400nF/4uF/40uF/100uF	
Temperature	-40 °C ~ 1000 °C	
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	± (0.5% +3)
Duty Cycle	0.1% ~ 99.9%	√
Special Features		
Diode test		√
Continuity Buzzer		√
NCV		√
Automatic shutdown		√
Low Voltage Display		√
Input impedance voltage measurement	≥ 10MΩ	
Data Retention		√
Maximum display		3999
General Characteristics		
Power	9V Battery (6F22)	
LCD size	49 * 18mm	
Body Color	Red + Gray	
Body Weight	About 200g (including batteries)	
Dimensions	72 * 137 * 35mm	
Standard accessories	Table pen, battery,	
Standard Packaging	Box, manual	
Standard Packing	60	
Standard Packaging Size	540 * 310 * 350mm	