

60W Waterproof AC-DC Switching Power Supply Specifications

	Model	W12V60W-S		Remark
Input	Voltage (V)	100V-260V		
	Current (A)	ACIN 110V 0,63		
		ACIN 220V 0,32		
	Frequency (Hz)	50Hz/60Hz (47~63Hz)		
	Efficiency	ACIN 110V 85%		
		ACIN 220V 85%		
	Inrush Current (A)	ACIN 110V 20 typ @ 25 °C cold start ACIN 220V 40 typ @ 25 °C cold start		
Output	Leakage current (A)	0.75max (ACIN 115V/240V, 60Hz, Io = 100%, IEC60950-1 and DEN-AN compliant)		
	Voltage (V)	12		
	Current (A)	ACIN 110V 5		
		ACIN 220V 5		
	Power (W)	ACIN 85-115V 60		
		ACIN 115-264V 60		
	Power Supply Regulation (mV)	200max		
	Load Regulation (mV)	120max		
	Ripple Voltage (mV p-p)	-10~50°C 200max		
	Ripple Noise (mV p-p)	-10~50°C ≤350mV		
	Drift (mV)	60max		
Protection circuit and	Startup time (ms)	≤200S@120VAC≤10S@230VAC		
	Protection time (ms)	≥20mS@120VAC, ≥20mS@230VAC		
	Output voltage range (V)	± 10% (rated output voltage)		
Insulation properties	Overcurrent protection	105% ~ 150% (rated load), self-recovery		
	Overvoltage protection (V)	115% ~ 135% (rated output voltage)		
	Short circuit protection	Protection, automatic recovery		
Environmental conditions	Input-output	AC1500V,1min, 25°C		
	Input-Enclosure	AC1500V,1min, 25°C		
	Output-Enclosure	DC500V,1min, 25°C		
	Operating temperature	-10°C~50°C; 20% ~ 90% RH (no condensation)		
Safety and noise regulation	Storage temperature	-20°C~70°C; 20% ~ 90% RH (no condensation)		
	Vibration	10 ~ 55Hz, 19.6m/S2 (2G), 3 min cycle, 60 min along X, Y, Z axis		
	Impact	196.1m/S2 (20G), 11ms, once along X, Y and Z axis		
Other	Safety certification	Comply with EN		
	Electromagnetic compatibility standard	EN55022 Class B, EN61000-4-2/-3/-4/-5/-6/-11		
	Enclosure dimensions	179*46*31mm		
	Weight (kg)	0,49		
	Cooling method	Natural Energy		