



T
5150
-
T
B
E
0
0
0
0
0
0
R

- | | | |
|--|--|---|
| <p>1. PRODUCTS: T: Terminal</p> <p>2. SERIES NO.: 5150 (Female Terminal)</p> <p>3. CONTACT PLATING: T: Tin</p> | <p>4. MATERIAL: B: Brass</p> <p>5. WIRE OPTION: E: Suitable For 18-24 Awg</p> <p>6. FILL IT WITH "0"</p> | <p>7. FILL IT WITH "0"</p> <p>8. FILL IT WITH "0"</p> <p>9. FILL IT WITH "0"</p> <p>10. FILL IT WITH "0"</p> <p>11. R: ROHS</p> |
|--|--|---|

Specification:
 Current Rating: 7A
 Voltage Rating: 600V
 Operating Temp: -25°C~+85°C
 Insulation Resistance: 100MΩ min
 Dielectric Withstanding Voltage: 1500V AC 1min
 Contact Resistance: 10mΩ

| | | |
|--|---|---|
| RoHS Compliant | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 Angel DWG 製圖 Yumi DATE 制表日 2010/01/06 |  SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1 | TOLERANCE 容許公差 .000 ±0.08 .00 ±0.13 .01 ±0.25 SIZE 板厚尺寸 A 4 REV 版次 B |
| PART NAME 品名 4.2mm FEMALE TERMINAL BRASS MATERIAL TIN PLATING 18-24AWG ROHS LOW-LEAD | | PART NO. 料號 T5150-TBE00000R |

| THICKNESS | MATERIAL | WIRE RANGE | INSULATION O.D. | FINISH |
|-----------|----------|------------|-----------------|-----------------|
| 0.2 | BRASS | AWG #18-24 | 2.1-1.4mm | PRE. TIN-PLATED |