Rated Voltage	DC3.7V	DC6V	DC12V				
Voltage Range	DC3V-4V	DC4.8V-7.2V	DC10.8V-13.2V				
Load Current	<550mA	<420mA	<280mA				
Power	<2W	<2W	<2W				
Pressure Range	-450mmHg~900mmHg(-60Kpa~120Kpa)						
Flow	≥2.8LPM						
Noise	Pump body underlay is 5cm thick sponge, placed on the noise meter 30cm ,Rated voltage under inflation pressure from 0 to 420mmHg the measured value is less than 60dB						
Life	Pumping 10 seconds, on 5 seconds for a cycle, test for 30,000 cycles , the under performance range is within 15%.						
Working Fluid	Air						
Operating Temperature Range	0°C-55°C						

DIRECTION OF RORATION Section 23-128 4-M3 20 64

技术参数 Technical Data

电压	空载转数	空載电流	额定转数	额定电流	额定转矩	堵转力矩	堵转电流
Voltage	No-losd Speed	No- load Current	Rated Speed	Rated Current	Rated Torque	Stall Torque	Stall Current
VDC	Rpm	Apm	Rpm	Amp	G. cm	G. cm	Amp
12V	2000	0.05	950	0.52	300	580	0.96
247	3000	0.06	1800	0.38	300	750	00.9
24V	4000	0, 08	1700	1.12	750	1305	1.9