



GK-25

GK SERIES METAL CASE SWITCHING POWER SUPPLY(25-100W)

Features

- Protections : Short circuit /overload/over voltage/ over temp.
- Cooling by free air convection
- 100% full load burn-in test
- 1 year warranty



MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-25-5	90-264VAC	5V@5A	110x78x36
GK-25-12	90-264VAC	12V@2.1A	110x78x36
GK-25-15	90-264VAC	15V@1.7A	110x78x36
GK-25-24	90-264VAC	24V@1.1A	110x78x36



GK-35

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-35-5	90-264VAC	5V@7A	129x98x40
GK-35-12	90-264VAC	12V@3A	129x98x40
GK-35-24	90-264VAC	24V@1.5A	129x98x40
GK-35-48	90-264VAC	48V@0.8A	129x98x40



GK-50

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-50-5	90-264VAC	5V/10A	129x98x40
GK-50-12	90-264VAC	12V/4.2A	129x98x40
GK-50-24	90-264VAC	24V/2.1A	129x98x40
GK-50-48	90-264VAC	48V/1.1A	129x98x40



GK-100

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-100-5	85-132Vac,185-264Vac	5V 20A	199x98x42
GK-100-12	85-132Vac,185-264Vac	12V 8.4A	199x98x42
GK-100-24	85-132Vac,185-264Vac	24V 4.2A	199x98x42
GK-100-48	85-132Vac,185-264Vac	48V 2.1A	199x98x42



GK-150

GK SERIES METAL CASE SWITCHING POWER SUPPLY(150-350W)

Features

- AC input range selected by switch
- Protections : Short circuit /overload/over voltage/ over temp.
- Cooling by free air convection for GK150 & GK200
- Forced cooling by buicd-in fan for GK300 & GK350
- 100% full load burn-in test
- 1 year warranty



GK-200

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-150-5	85-132Vac,185-264Vac	5V 30A	199x110x50
GK-150-12	85-132Vac,185-264Vac	12V 12.5A	199x110x50
GK-150-24	85-132Vac,185-264Vac	24V 6.5A	199x110x50
GK-150-48	85-132Vac,185-264Vac	48V 3.2A	199x110x50



GK-300

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-200-5	85-132Vac,185-264Vac	5V 40A	199x110x50
GK-200-12	85-132Vac,185-264Vac	12V 16.7A	199x110x50
GK-200-24	85-132Vac,185-264Vac	24V 8.4A	199x110x50
GK-200-48	85-132Vac,185-264Vac	48V 4.2A	199x110x50



GK-350

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-300-5	85-132Vac,185-264Vac	5V 40A	215x115x50
GK-300-12	85-132Vac,185-264Vac	12V 16.7A	215x115x50
GK-300-24	85-132Vac,185-264Vac	24V 8.4A	215x115x50
GK-300-48	85-132Vac,185-264Vac	48V 4.2A	215x115x50

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-350-5	85-132Vac,185-264Vac	5VDC@70A	215x115x50
GK-350-12	85-132Vac,185-264Vac	12VDC@29.5A	215x115x50
GK-350-24	85-132Vac,185-264Vac	24VDC@14.6A	215x115x50
GK-350-48	85-132Vac,185-264Vac	48VDC@7.3A	215x115x50



GK-600

GK SERIES METAL CASE SWITCHING POWER SUPPLY (600-2000W)

Features

- Protections : Short circuit /overload/over voltage/ over temp.
- Forced air cooling by build-in fan
- 100% full load burn-in test
- 1 year warranty



MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-600-5	180-260Vac	5VDC@50A	291x133x68
GK-600-12	180-260Vac	12VDC@21A	291x133x68
GK-600-24	180-260Vac	24VDC@10.5A	291x133x68
GK-600-48	180-260Vac	48VDC@5.3A	291x133x68



GK-800/1000

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-800-12	180-260Vac	5VDC@60A	291x133x68
GK-800-15	180-260Vac	12VDC@25A	291x133x68
GK-800-24	180-260Vac	24VDC@12.5A	291x133x68
GK-800-48	180-260Vac	48VDC@6.3A	291x133x68
GK-1000-12	180-260Vac	12VDC@83.3A	291x133x68
GK-1000-24	180-260Vac	24VDC@41.6A	291x133x68
GK-1000-48	180-260Vac	48VDC@20.8A	291x133x68



GK-1200/1500

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-1200-12	180-260Vac	12VDC@100A	291x132x132
GK-1200-24	180-260Vac	24VDC@50A	291x132x132
GK-1200-48	180-260Vac	48VDC@25A	291x132x132
GK-1500-12	180-260Vac	12VDC@125A	291x132x132
GK-1500-24	180-260Vac	24VDC@62.5A	291x132x132
GK-1500-48	180-260Vac	48VDC@31.5A	291x132x132



GK-2000

MODEL	INPUT	OUTPUT	DIMENSION(mm)
GK-2000-12	180-260Vac	12VDC@166.7A	320x212x134
GK-2000-24	180-260Vac	24VDC@83.4A	320x212x134
GK-2000-48	180-260Vac	48VDC@41.7A	320x212x134



DK-35

DK SERIES METAL CASE SWITCHING POWER SUPPLY (35-100W)

Features

- Small size
- Protections : Short circuit /overload/over voltage/ over temp.
- Cooling by free air convection
- 100% full load burn-in test
- 1 year warranty



MODEL	INPUT	OUTPUT	DIMENSION(mm)
DK35-05	100Vac-240Vac	5V/5.00A	85*59*37
DK35-12	100Vac-240Vac	12V/3.00A	85*59*37
DK35-13.8	100Vac-240Vac	13.8V/2.60A	85*59*37
DK35-15	100Vac-240Vac	15V/2.40A	85*59*37
DK35-24	100Vac-240Vac	24V/1.50A	85*59*37
DK35-36	100Vac-240Vac	36V/1.00A	85*59*37
DK35-48	100Vac-240Vac	48V/0.80A	85*59*37



DK-50

MODEL	INPUT	OUTPUT	DIMENSION(mm)
DK50-05	100Vac-240Vac	5V/8.00A	110*78*36
DK50-12	100Vac-240Vac	12V/4.20A	110*78*36
DK50-13.8	100Vac-240Vac	13.8V/3.60A	110*78*36
DK50-15	100Vac-240Vac	15V/3.30A	110*78*36
DK50-24	100Vac-240Vac	24V/2.10A	110*78*36
DK50-36	100Vac-240Vac	36V/1.39A	110*78*36
DK50-48	100Vac-240Vac	48V/1.05A	110*78*36



DK-70

MODEL	INPUT	OUTPUT	DIMENSION(mm)
DK70-05	100Vac-240Vac	5V/10.00A	129*98*40
DK70-12	100Vac-240Vac	12V/5.83A	129*98*40
DK70-13.8	100Vac-240Vac	13.8V/5.07A	129*98*40
DK70-15	100Vac-240Vac	15V/4.67A	129*98*40
DK70-24	100Vac-240Vac	24V/2.92A	129*98*40
DK70-36	100Vac-240Vac	36V/1.94A	129*98*40
DK70-48	100Vac-240Vac	48V/1.46A	129*98*40



DK-100

MODEL	INPUT	OUTPUT	DIMENSION(mm)
DK100-05	100Vac-240Vac	5V/16.00A	159*98*42
DK100-12	100Vac-240Vac	12V/8.33A	159*98*42
DK100-13.8	100Vac-240Vac	13.8V/7.25A	159*98*42
DK100-15	100Vac-240Vac	15V/6.67A	159*98*42
DK100-24	100Vac-240Vac	24V/4.17A	159*98*42
DK100-36	100Vac-240Vac	36V/2.78A	159*98*42
DK100-48	100Vac-240Vac	48V/2.08A	159*98*42



DKP-100

DKP SERIES METAL CASE SWITCHING POWER SUPPLY (100-320W)

Features

- Built-in active PFC function, PFC>0.9
- Protections : Short circuit /overload/over voltage/ over temp.
- Cooling by free air convection for DKP100, DKP150 & DKP200
- Forced cooling by buicd-in fan for DKP320
- 100% full load burn-in test
- 1 year warranty



DKP-150

MODEL	INPUT	OUTPUT	DIMENSION(mm)
DKP100-05	100Vac-240Vac	5V/20A	179*99*45
DKP100-12	100Vac-240Vac	12V/8.3A	179*99*45
DKP100-13.8	100Vac-240Vac	13.8V/7.2A	179*99*45
DKP100-15	100Vac-240Vac	15V/6.6A	179*99*45
DKP100-24	100Vac-240Vac	24V/4.2A	179*99*45
DKP100-36	100Vac-240Vac	36V/2.8A	179*99*45
DKP100-48	100Vac-240Vac	48V/2.1A	179*99*45



DKP-200

MODEL	INPUT	OUTPUT	DIMENSION(mm)
DKP150-05	100Vac-240Vac	5V/30.0A	199*99*50
DKP150-12	100Vac-240Vac	12V/12.5A	199*99*50
DKP150-13.8	100Vac-240Vac	13.8V/10.8A	199*99*50
DKP150-15	100Vac-240Vac	15V/10.0A	199*99*50
DKP150-24	100Vac-240Vac	24V/6.2A	199*99*50
DKP150-36	100Vac-240Vac	36V/4.2A	199*99*50
DKP150-48	100Vac-240Vac	48V/3.1	199*99*50



DKP-320

MODEL	INPUT	OUTPUT	DIMENSION(mm)
DKP200-05	100Vac-240Vac	5V/40.0A	199*99*50
DKP200-12	100Vac-240Vac	12V/16.6A	199*99*50
DKP200-13.8	100Vac-240Vac	13.8V/14.5A	199*99*50
DKP200-15	100Vac-240Vac	15V/13.3A	199*99*50
DKP200-24	100Vac-240Vac	24V/8.3A	199*99*50
DKP200-36	100Vac-240Vac	36V/5.5A	199*99*50
DKP200-48	100Vac-240Vac	48V/4.2A	199*99*50

MODEL	INPUT	OUTPUT	DIMENSION(mm)
DKP320-05	100Vac-240Vac	5V/50.0A	215*115*50
DKP320-12	100Vac-240Vac	12V/25.0A	215*115*50
DKP320-13.8	100Vac-240Vac	13.8V/21.5A	215*115*50
DKP320-15	100Vac-240Vac	15V/20.0A	215*115*50
DKP320-24	100Vac-240Vac	24V/12.5A	215*115*50
DKP320-36	100Vac-240Vac	36V/8.8A	215*115*50
DKP320-48	100Vac-240Vac	48V/6.6A	215*115*50