



NOTE:

1. MATERIAL:

- a. HOUSING: LCP GLASS FIBRE UL94 V-0
- b. CONTACT: COPPER T=0.25mm
(SURFACE PLATING: Au100u" + Sn100u" + Ni60u")
- c. SHEEL: COPEER ALL T=0.30mm
(SURFACE PLATING: Ni100u" ~ 120u")

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -55° ~ 105°

RECOMMENDED PCB LAYOUT
TOLERANCE: ± 0.05

NINGBO KLS ELECTRONIC CO., LTD

DIMENSIONS INIT: mm UNLESS OTHERWISE SPECIFIABLE DIMENSION TOLERANCE X.X: ± 0.38 X.XX: ± 0.25 X.XXX: ± 0.10 ANGULAR: ± 1°	PRODUCT NAME :	HDMI A TYPE SMT SHELL DIP	DRAWING:	COCO	DATE:	2018/08/11
	PRODUCT NO. :	L-KLS1-285-1-N-1-R	CHECK:	JANY	DATE:	2018/08/11
	DRAWING NO. :		APPROVED:	JEFF	DATE:	2018/08/11
			SCALE:	NA	DWG ID:	REV.:
				P D	A	1 OF 1

REVISION NO.	ECR NO.	DESCRIPTION	MARK	DATE
1				
2				
3				