

Digital Clamp Meter - True RMS

MS2003B



- Frequency: 1000Hz
- True RMS
- Duty Cycle
- AC/DC voltage
- V.F.C
- Diode
- Continuity Check
- Non-Contact Voltage (NCV) Detection / Live Wire (Live) Recognition
- Max Display: 6000
- CAT III 600V
- Input Impedance $\geq 10M\Omega$
- Max Jaw Opening: 19mm
- Auto Power Off
- Data Hold
- Backlight
- Unit Display
- Battery: 1.5V AAA*2

MS2003B

Spec	Range	Accuracy	Spec	Range	Accuracy
Resistance	600 Ω	$\pm(4.0\%+10)$	°C	-20 °C ~ 0 °C	± 4 °C
	6K Ω , 60K Ω , 600K Ω , 6M Ω	$\pm(0.8\%+5)$		0 °C ~ 400 °C	$\pm(2.0\%+3)$
	60M Ω	$\pm(2.0\%+10)$		400 °C ~ 1000 °C	$\pm(3.0\%+3)$
DC Voltage	600mV	$\pm(0.7\%+5)$	°F	-4 °F ~ 50 °F	± 5 °F
	6V, 60V, 600V	$\pm(0.8\%+5)$		50 °F ~ 750 °F	$\pm(2.0\%+5)$
	600mV	$\pm(1.0\%+10)$		750 °F ~ 1832 °F	$\pm(3.0\%+5)$
AC Voltage	600mV	$\pm(1.0\%+10)$	Capacitance	10nF	$\pm(4.0\%+25)$
	6V, 60V, 600V	$\pm(1.0\%+5)$		100nF ~ 100uF	$\pm(4.0\%+15)$
	V.F.C 600V	$\pm(4.0\%+5)$		1mF ~ 60mF	$\pm(5.0\%+25)$
AC Current	6000mA, 60A, 200A	$\pm(2.5\%+10)$	Frequency	10Hz ~ 1KHz	$\pm(0.5\%+2)$

Packaging Information	
Accessories	Carry bag, Test leads, Manual, Temperature probe, 1.5V*2 AAA Battery
Dimension	60mm*178mm*32mm
Weight	165g
Quantity	40
Color Box	75mm*55mm*195mm
Carton Box	400mm*315mm*395mm
SKU No.	MS2003BCBGLO
EAN Code	8435394788371

MGL Global Solutions (China) Company Limited

R72, Puxing East Road, Qingxi, Dongguan, Guangdong, China
 400-099-1987
 cs@mastech.cn



www.mastech-group.com