

DIGITAL THERMOMETER

MS6513/MS6514

Features:

- ▶ Large Dual LCD Display
- ▶ Resolution: 0.1°C, 0.1°F, 0.1K
- ▶ Built-In Ambient Temperature Compensation
- ▶ Auto Power Off
- ▶ MAX/MIN/AVG and Data Hold
- ▶ USB Interface and Analysis Software

Specifications	MS6513	MS6514
Specifications		
Thermocouple Type	K, J, T, E, R, S, N	K, J, T, E, R, S, N
Channel	Single	Dual
Measurement Range	K : -200.0°C to +1372°C / -328.0°F to +2501°F	
	J : -210.0°C to +1200°C / -346.0°F to +2192°F	
	T : -250.0°C to +400°C / -418.0°F to +752°F	
	E : -150.0°C to +1000°C / -238.0°F to +1832°F	
	R : 0°C to +1767°C / 32°F to +3212°F	
	S : 0°C to +1767°C / 32°F to +3212°F	
Accuracy	K, J, T, E : ±(0.2%+0.5°C)	
	R, S : ±(0.2%+1°C)	
	N : ±(0.2%+0.5°C)	
Data Logging	1000 groups	
Ambient Temperature Compensation	●	
Auto Power Off	●	
MAX/MIN/AVG	●	
DATA Hold	●	
USB Interface	●	
General		
Power Supply	1x9V 6F22 Battery	
Product Size	190mm×89mm×42mm/7.5"×3.5"×1.7"	
Product Weight	350g/0.8lb	



MS6513

TYPE

K, J, T, E, R, S, N

RESOLUTION

0.1°C, 0.1°F, 0.1K

°F/°C

MEM

Apo

MAX

MIN

USB



MS6514

TYPE

K, J, T, E, R, S, N

RESOLUTION

0.1°C, 0.1°F, 0.1K

°F/°C

MEM

Apo

MAX

MIN

USB