

DIGITAL MULTIMETER

MY63/MY64/MY65

Features:

- ▶ Rugged Shell Design
- ▶ Large Digital LCD Display
- ▶ Tests AC/DC Voltage and Current, Resistance, Capacitance and Frequency
- ▶ Transistor Check, Diode and Continuity Test
- ▶ Type-K thermocouple contact temperature measurement (MY64)
- ▶ Data Hold and Auto Power Off

EMC
LVD



Specifications

Specifications	Range	MY63	MY64	MY65
DC Voltage	200mV/2V/20V/200V	±(0.5%+3)	±(0.5%+3)	±(0.1%+3)
	1000V	±(0.8%+3)	±(0.8%+3)	±(0.15%+3)
AC Voltage	2V/20V/200V	±(0.8%+3)	±(0.8%+3)	±(0.6%+10)
	750V	±(1.2%+3)	±(1.2%+3)	±(0.8%+15)
DC Current	2mA/20mA/200mA	±(1.5%+1)	±(1.5%+1)	±(0.8%+5)
	10A	±(2.0%+5)	±(2.0%+5)	±(2.0%+10)
AC Current	2mA/20mA/200mA	±(1.8%+5)	±(1.8%+5)	±(0.8%+10)
	10A	±(3.0%+5)	±(3.0%+5)	±(2.0%+10)
Resistance	200Ω/2KΩ/20KΩ/200KΩ/2MΩ	±(0.8%+3)	±(0.8%+3)	±(0.5%+3)
	20MΩ	±(1.0%+5)	±(1.0%+5)	±(0.5%+1)
	200MΩ	±(6.0%+10)	±(6.0%+10)	±(5.0%+10)
Capacitance	2nF/20nF/200nF/2μF	±(4.0%+3)	±(4.0%+3)	
	20nF/200nF/2μF/20μF			±(4.0%+20)
Frequency	100μF	±(6.0%+10)	±(6.0%+10)	±(6.0%+10)
	20kHz		±(1.5%+5)	±(1.5%+5)
	2kHz/20kHz	±(1.5%+5)		
Temperature(°C)	-20°C~1000°C		±(2%+2)	
Functions				
Display	counts	2000	2000	20000
Transistor hFE	0~1000	●	●	●
Diode	2.7V	●	●	●
Continuity Buzzer	<50Ω	●	●	●
Data Hold		●	●	●
Apo	Auto Power Off	●	●	●
LBD	Low Battery Display	●	●	●
General				
Power Supply	1x9V 6F22 Battery			
Product Size	195mmx95mmx55mm/7.67"×3.74"×2.16"			
Product Weight	366g/0.8lb			
Safety Rating	CE ETL CAT.II 1000V CAT.III 600V RoHS			



MY63

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A



MY64

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A



MY65

VOLTAGE AC 750V
DC 1000V

CURRENT AC 10A
DC 10A

