



**SPECIFICATIONS**

Current Rating: 1A AC,DC  
 Voltage Rating: 50V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max.  
 Insulation Resistance: 100MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Material: PBT,UL94V-0  
 Color: Natural(White)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
A1001H-02P-1	1.00	5.00
A1001H-03P-1	2.00	6.00
A1001H-04P-1	3.00	7.00
A1001H-05P-1	4.00	8.00
A1001H-06P-1	5.00	9.00
A1001H-07P-1	6.00	10.00
A1001H-08P-1	7.00	11.00
A1001H-09P-1	8.00	12.00
A1001H-10P-1	9.00	13.00
A1001H-11P-1	10.00	14.00
A1001H-12P-1	11.00	15.00
A1001H-13P-1	12.00	16.00
A1001H-14P-1	13.00	17.00
A1001H-15P-1	14.00	18.00
A1001H-16P-1	15.00	19.00
A1001H-17P-1	16.00	20.00
A1001H-18P-1	17.00	21.00
A1001H-19P-1	18.00	22.00
A1001H-20P-1	19.00	23.00
A1001H-24P-1	23.00	27.00

						JOINT TECH ELECTRONIC IND. CO., LTD.			
				JOY DAY INDUSTRIAL CO., LTD.					
				UNIT	SCALE	SHEET	TITLE:		
				mm		1 of 1	1.00mm PITCH		
B5	REVISE	2009.05.25		DRAWN BY		APPROVED BY	HOUSING		
B4	REVISE	2008.12.17		董正一		董正一	WITH PROTRUSIONS		
B3	REVISE	2008.10.24		2001.03.27		2001.03.27			
B2	REVISE	2007.06.14		GENERAL TOLERANCE					
B1	REVISE	2006.10.10		X. X±0.25		ANGLE±			
B0	NEW RELEASE	2006.04.14		X. XX±0.15					
REV.	DESCRIPTION	DATE		X. XXX±0.05			DRAW NO.:	A1001H-XP-1	REV. B5